

UB1229-T

Maintenance-Free



POWERSTRIDE BATTERY



Specification

Nominal Voltage	12 volts		
Nominal Capacity	77° F (25° C)		
20-hr. (0.145A)	2.7 Ah		
10-hr. (0.27A)	2.9 Ah		
5-hr. (0.5A)	2.47 Ah		
1-hr. (1.74A)	1.74 Ah		
Approximate Weight	2.59 lbs (1.18 kg)		
Internal Resistance (approx.)	15mΩ		
Shelf Life (% of normal capacity at 77° F (25° C))			
3 Months	6 Months	12 Months	
91%	82%	64%	
Temperature Dependency of Capacity	(20 hour rate)		
104° F	77° F	32° F	5° F
102%	100%	85%	65%

Charge Method (Constant Voltage)


Cycle Use (Repeating Use)

Initial Current	0.7 A or smaller
Control Voltage	14.5-14.9 V

Float Use


Control Voltage	13.5-13.8 V
-----------------	-------------

Physical Dimensions: in (mm)




L: 3.11in (79 mm)
W: 2.32in (59 mm)
H: 3.90in (99 mm)
TH: 4.21in (107 mm)
 Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

Terminals




Dimension Type	L	W	w	H	T
F1	6.50	4.75	6.00	5.00	0.80

Discharge Characteristics (25° C, 68° F)




Discharge Characteristics (0° C, 32° F)




UB1229-T

Maintenance-Free


Shelf Life & Storage




Cycle Life vs Depth of Discharge



Open Circuit Voltage vs Residual Capacity



Effect of Temperature on Capacity



Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current	Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
	Temperature	Set Point	Allowable Range						
Cycle Use	25°C(77°F)	2.45	2.40~2.50	0.35C	Discharge Current(A)	0.2C<(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C
Standby	25°C(77°F)	2.325	2.30~2.35						

